


Suggested P.C.B Layout

CIRCUIT:



Specifications	
Rating	0.1A 12VDC
Environment Temperature	-25°C ~ 85°C
Contact Resistance	< 50mΩ
Insulation Resistance	> 100MΩ
Withstand Voltage (normal proof)	100V AC/10mA/5s
Electrostatic life	500V AC/10mA/5s
Operating Force	100,000 Cycles
	2 ± 0.5N

Model NO.	dimensions (H) /mm
TC-0606AL	4.3
TC-0606AL-01	5
TC-0606AL-02	7
TC-0606AL-03	8.0
TC-0606AL-04	9.5
TC-0606AL-05	11
TC-0606AL-05	13
TC-0606AL-05	21

NOTE:

TOLERANCE UNLESS OTHERWISE SPECIFIED
 X. ± 0.30 . X ± 0.20 . XX ± 0.15

Product Drawing

标记/代号	更改文件号	签名	日期	投影 共 1 页	版次 A0	重量 8:1(40)	比例 8:1(40)
设计	标准化						
审核	批准						
工艺	日期						
ZHEJIANG JIANGONG ELECTRON CO., LTD Tact Switch				11-TC-0606AL			

值 (通) 用序號記
旧版圖號号
版圖號号
簽名
日期