



REV	E.C.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	16.11.14

- NOTES:
- Rating: 300V/16A
<IEC> 320V/20A
 - Poles:02-24P
 - Insulation Withstands Voltage: AC2000V/1 Min
 - Contact resistance: 20mΩ
 - Insulation Resistance: 500MΩ at DC500V
 - Using Temperature Range: -40°C/+115°C
 - Max soldering : +250° for 5S
 - RoHS Compliance.
 - With "★" "is import dimension"

How to order

ULO-TB27 - 2VC/5.08 - □□P -Y 0 0 0 A

Certificate Series NO. Factory Code poles color: Customer requirements (standard)

- 1:Grey
- 2:Blue
- 3:Black
- 4:Green
- 5:Orange
- 6:Red
- 7:transparent
- 8:Yellow
- 9:White

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	-	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		

2	Solde pin	1002B0010	N	BRASS	Sn Plated
1	Housing	1006A0YXXA	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	2016.11.14	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
NINGBO ULO ELECTRONICS CO.,LTD.			NAME	ULO-TB27-2VC/5.08-XXP-Y000A	
宁波欧路电子有限公司			DRAWING NO.	ULOTB27Y000A	