

12.1" PCAP All-in-One Touch Computer

TC-1262



TC-1262 is 12.1inch project capacitive All-in-One touch computer Aluminum alloy front bezel,inside pcap touch meet IP65 wateproof, Highlight display with anti-vandal tempered cover glass meet UL60950, Suitable for outdoor application,which is designed for Kisoks,Interactive digital signage,ATM,Gaming.Casino,Industrial,Education etc., is easily connected and installed by user.

Features

Zero-bezel flat touch computer, slim housing
High brightness LED panel
10Point multitouch project capacitive touch technology
3mm anti-vandal tempered cover glass meet UL60950 steel ball test
Aluminum alloy front bezel, meet IP65 waterproof
Efficient and stable intel computer system
Standard VESA mounting and four side bracket options

TC-1262 12.1inch PCAP All-in-One Touch Computer Specification





Product Model		TC-1262
Product Description		12.1" PCAP All-in-One Touch Computer
DISPLAY	Display	12.1 " 4:3 Active Matrix TFT LCD
	Useful Screen Area	248.6mm x 187mm
	Optimal Resolution	1024 x 768
	Number of colors	16.7 million
	Brightness	300 cd/m2
	Contrast Ratio	700:1 (Typical)
	Response Time	5ms (Typically)
	Viewing Angle	Horizontal: ±80°or 160°total
		Vertical: ±80°or 160°total
	CPU	Celeron J1900 1.99GHz(Intel i3,i5,i7 options)
	RAM	4G
	Harddisk	128 SSD or 500G STAT
	USB and COM Port	2 x USB 3.0, 2 x USB 2.0,2 x COM(RS232) port
	Ethernet Port	1 x LAN RJ45(Gigabit)
	Additional Video Out	1 x HDMI and 1 x VGA out
	Wireless	Wi-Fi 802.11 a/b/g/n/ac
	Bluetooth	Bluetooth 4.0
	Audio and Microphone	1 x 3.5mm line out, and 1 x microphone out
	Speaker	2x 12W internal speakers
TOUCH	Touch Technology	Project capacitive touch technology
	Response Time	3ms
	Touch Resolution	32767 x 32767
	Touch Glass	3mm Anti-vandal tempered glass meet UL60950 IK07
Sealability		Touchscreen sealed to Aluminum alloy-bezel IP65
		Touchscreen sealed to LCD
MTBF		50,000 hours demonstrated
Mounting Options		VESA Mount, four-side bracket and stand option
Power Supply		100-240VAC, 50-60Hz
Temperature Range		Operating: 0°C to 50°C; Storage: -20°C to 60°C
Humidity Range (no condensing)		Operating: 20%-80%; Storage: 10%-90%
Product Dimension		307.5mm x 247mm x 48.8mm
Warranty		1 year
Agency Approvals		FCC, CE, RoHS

