


Suggested P.C.B Layout

技术参数/Specifications	
额定参数/Rating	0.1A 12VDC
环境温度/Environment Temperature	-25°C ~ 85°C
接触电阻 Contact Resistance	≤ 50mΩ
绝缘电阻/Insulation Resistance	≥ 100MΩ (at 500VDC)
耐电压 Withstand Voltage	100V AC/10mA/5s
电气寿命 Electrical life	500V AC/10mA/5s
操作力 Operating force	100000 Cycles
	250gf

电气原理图:
CIRCUIT:



NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 . X ± 0.20 . XX ± 0.10

修改日期/修改记录 MODIFY DATE	
审核日期/审核记录 CHECK DATE	
设计日期/设计记录 DESIGN DATE	
制图日期/制图记录 DRAWING DATE	
文件编号 FILE NO.	
图号 DRAWING FILE NO.	
零件号 PART NO.	
名称 NAME	

成品图 PRODUCT DRAWING				浙江佳龙电子有限公司 ZHEJIANG JIALONG ELECTRON CO., LTD	
图号 DRAWING NO.	更改文件号 REVISE FILE NO.	版本号 VERSION	日期 DATE	投影 PROJECTION	重量 WT.
设计 DESIGN	审核 CHECK	制图 DRAWING	日期 DATE	比例 SCALE	页次 PAGE
工 ARTWORK	DATE	DATE	DATE	1:1 (A4)	11-TC-06F
				11-TC-06F	