

REVISION RECORD			
REV	ECN	DESCRIPTION	DRFT DATE

NOTES1:

UL Standard

1. Rated voltage/current : 300V / 8A
2. Withstanding voltage : AC1600V/1Min.
3. Torque value : M2, 1.77Lb.in
4. Wire range : 28~16AWG

IEC Standard

Pollution degree	2
Overvoltage category	II
Rate impulse voltage(KV)	2.5KV
Rate voltage(V)	250V
Rate current(A)	7A

2. Torque value : M2, 0.2N·m
3. Wire range : 0.5~1.5mm²

NOTES2:

1. Dimension shall be interpreted per ASME Y14.5-2009
2. Pitch : 3.5/3.81mm, Poles : N=02~24P
3. Stripping length : 6~7mm
4. Operating temperature: -40°C~+105°C
5. Undimensioned tolerances:

Pitch range in mm		Nominal dimension range		Tolerance	
Over	TO	Over	TO	Over	TO
6	10	30	60	100	150
6	10	24	30	60	100
±0.15	±0.20	±0.30	±0.50	±0.70	±1.00
		±1.00	±1.30	±2*	

6. RoHS Compliance


15EDGK - 3.5/3.81 - XXP - 1Y - 00A (H)

(Series No.) (Pitch) (Poles) (Color): 1.(Grey)
2.(Blue)
3.(Black)
4.(Green)
5.(Orange)
6.(Red)
7.(Transparent)
8.(Yellow)
9.(White)

(Single Pitch)

00A - (Standard)
L(RoHS)

PART NO.:	/	DEGSON®	NINGBO DEGSON ELECTRICAL CO., LTD
APPD:	/	NAME:	15EDGK-3.5/3.81-XXP-1Y-00A(H)
CHKD:	/	TITLE:	CUSTOMER DRAWING
DRFT:	/	DRAWING NO.:	/
THIRD ANGLE PROJECTION		DO NOT SCALE	DRAWING SCALE
1:1		1:1	1:1



02~06P have this card point

