

MTX-IoT-XS

Basic 4G/3G/2G programmable IoT modem

MTX-IoT-XS is an innovative and powerful all-in-one solution. Thanks to its set of interfaces (RS232, RS485, USB, digital I/O...) and the embedded MTX-Tunnel firmware that provides the MTX-IoT-XS with a basic router-like functionality, this modem can be used in most of the IoT applications with no need for further hardware, shortening the time-to-market and providing a very cost-effective solution. MTX-IoT-XS can be also programmed in JavaJ2ME, for those customers who want to embed their own firmware on it.



MAIN FEATURES



4G/3G/2G



USB 2.0



Up to 2x RS232
(see options)



RS485
(see options)



1x digital
input



1x digital
output



4G/3G/2G
serial gateway



GPIO
management



Datalogger



DynDNS
and No-IP



MQTT/s



Modbus
TCP/RTU



SMS
control

● Hardware features

● MTX-Tunnel software features

CERVELLO STEM - IOT PLATFORM FREE FOR ONE YEAR WITH MTX DEVICES*



Autoprovisioning



Alarms and
Alerts



Remote Control



Real time
Dashboards



Rules engine



Monitoring
engine



Analytics



Remote
update

*Available with compatible devices that have MTX-Tunnel or MTX-Titan

-  DC input: 7 to 36VDC
-  Temperature range: -30° to +85°C
-  Dimensions: 78x31x84mm
-  Weight: 131gr

Datasheet subject to changes | 2020/09
 MTX © by MATRIX ELECTRONICA S.L.U.
 SUPPORT: iotssupport@mtx2m.com
 SALES: info@mtx2m.com
mtx2m.com


HARDWARE FEATURES

MTX-IoT-XS 4G

| | |
|---|--|
|  | LTE 5 Bands (700, 800, 900, 1800, 2100MHz), GSM/GPRS/EDGE: 2 Bands (900, 1800MHz) |
|  | LTE Cat.1: DL 10.2Mbps, UL 5.2Mbps |
|  | HSPA: DL 7.2Mbps, UL 5.7Mbps UMTS PS: DL 384Mbps, UL 384 Mbps, CS: DL 64Mbps, UL 64Mbps |
|  | EDGE Class 12 data rates, DL: max. 237 kbps, UL: max. 237 kbps GPRS Class 12 data rates, DL: max. 85.6 kbps, UL: max. 85.6 kbps |
|  | CSD data transmission up to 9.6 kbps, V.110, non-transparent |
|  | SMS: text and PDU mode support, point-to-point MO and MT, cell broadcast |

Interfaces

-  4G/3G/2G connectivity
-  SIM card interface 1.8V and 3V
-  USB 2.0
-  Up to 2x RS232 (see options)
-  RS485 (see options)
-  1x digital input
-  1x digital output
-  Power supply
-  Operating status LEDs



Connectors

-  1x SMA F antenna connector: 4G
-  Mini USB B
-  RJ45 (COM1): RS232, 1x input, 1x output
-  RJ45 (COM2): RS232 or RS485 (check options)
-  RJ11: power supply 7-36V

MTX-TUNNEL SOFTWARE FEATURES

Connectivity



4G/3G/2G serial gateways: TCP client, TCP server, UDP client/server, accept incoming CSD calls, up to 2 simultaneous tunnel



IP connectivity mode: permanent 100% time, under request (SMS, missed call), change on a digital input, analog input out of level, serial data on RS232/RS485 port, scheduled date/hour/time

TCP Services



Web server, Telnet, SNMP, Tacacs+, NTP



Datalogger: MQTT, MQTTs, HTTP, HTTPs, FTP



Shows the status of digital and analog inputs



Change digital output level and relays



Execute AT commands remotely: Telnet, MQTT/MQTTs, SMS, HTTP

Security



Authorized phone numbers



Firewall IP, SSL/TLS connections, encrypted config



Secure OTAP (remote FIU upgrade)



Watchdog hardware

Alarms and Control



Send SMS/MQTT alarm when the level of digital or analog input change



SMS can be sent to up to 10 remote users



Execute remote AT commands



Change the status of digital outputs & relays



Customizable SMS commands

Solutions for Dynamic IP



IP session using a SMS or missed call



DynDNS and NoIP



Private DNS

Metering, Modbus, Sensors...



868 MHz remote monitoring sensors (Wavenis)



Master for modbus RTU devices, Modbus TCP slave, Modbus TCP to RTU gateway



Relays control



Access to serial devices using 2G/3G/4G and GSM



Astronomical clock

*MTX-Tunnel features depending on modem interfaces

ORDERING INFORMATION


MTX-IoT-XS [4-N]

199801473

MTX-IoT-XS [4-D]

199801475



MTX - IoT-XS [X - Options]





CERVELLO STEM - IOT PLATFORM

FREE FOR ONE YEAR WITH MTX DEVICES**



General Features

-  Up to unlimited devices
-  Autoprovisioning
-  Real time dashboards
-  Remote control
-  Monitoring engine
-  Alarms and alerts
-  Rules engine
-  Remote update
-  Connect engine*
-  API Keys*
-  Analytics*
-  Multi-tenant*
-  White labeling*
-  Custom admin role*

Monitor

-  Alarms, Events and Incidents
-  Tracking*

Control

-  Command template
-  OTA

Devices Inventory

-  Add single and single from template
-  Add Bulk from template and from autoprovisioning
-  Manage: Device template, Groups, Assets and Bulk actions

Connect

-  Topics*
-  Transformation*
-  Integration keys*

Visualize

-  Dashboards
-  Reports

Automate

-  Rules Engine
-  Actions
-  Triggers

Security

-  2-factor authentication
-  SSL for end user application
-  Custom admin roles*

*Upgrade required

**Available with compatible devices with MTX-Tunnel or MTX-Titan

