

FCHX1507-X430L0

Specification

Stretched Display, IP66 Chassis 15.1" LCD monitor, 1280x248, 300nits



Features

- Modular mechanism design provides flexible product configuration and easy maintenance.
- Optional with auto-brightness sensor offers application in day and night
- Optional to built-in PC eliminates external box.

| | | | |
|---------------------|--|---|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Size | 15.1" viewable diagonal area | |
| | Active Area / Pixel Pitch | 376.32(H) x 72.91(V) mm / 0.294(H) x 0.294(V) mm | |
| | Native Resolution / Colors | 1280(H) x 248(V) / 16.7 Million | |
| | Brightness / Contrast | 300 cd/m ² (typ) / 2000 : 1 | |
| | Response Time | ≤ 8 ms(G to G) | |
| | Viewing Angle (typical) | H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°) | |
| | Light Source | LED BLU , Long life, 35,000 hrs (typ) | |
| Input Sources | PC System | Signal | Analog RGB (0.7/1.0 V _{p-p} , 75 ohms) |
| | | Sync | Separate Sync, Composite Sync, Sync On Green |
| | | Frequency | F _H : 30 - 82Khz , F _V : 50 -75Hz |
| | Audio System | 3W speaker x 2 | |
| Input Terminals | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug | | |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B) | | |
| | OSD Multi-Languages , Wall Mount Ready | | |
| Power | 12V DC in | | |
| Power Consumption | Operation / Power Saving | 20 watt , < 2 watt (Support DPMS) | |
| Operating Condition | Temperature / Humidity | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation) | |
| Storage Condition | Temperature / Humidity | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) | |
| Certification | FCC , CE | | |
| Dimensions | Physical | With Base(W x H x D) : TBD | |
| | | Without Base(W x H x D) : 401.7 x 116.9 x 61.0 (mm) | |
| | Carton | W x H x D = TBD | |
| Weight | N.W. / G.W. | TBD | |

| | | |
|---------|----------------------|------------------------------|
| Options | Video / TV | Others |
| | SV + AV | Digital Signage(Stand alone) |
| | SV + AV + AV_Looping | Networking Digital Signage |
| | SV + AV + TV | Motion Sensor |
| | | Light Sensor |
| | | Auto-Dimming |

Winsonic[®]

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com