



- 技术参数 SPECIFICATIONS
- ◆ 适用线规: AWG.#16~#22
 - ◆ Applicable Wire: AWG.#16~#22
 - ◆ 额定电压: 250V DC/AC(rms)
 - ◆ Rated voltage: 250V DC/AC(rms)
 - ◆ 额定电流: 7A(AWG.#18)
 - ◆ Rated Current: 7A(AWG.#18)
 - ◆ 耐压值: 1500V AC/minute
 - ◆ Withstand voltage: 1500V AC/min.
 - ◆ 工作温度: -25°C ~ +85°C
 - ◆ Working Temp : -25°C ~ +85°C
 - ◆ 绝缘电阻: ≥1000 MΩ
 - ◆ Insulation resistance: ≥1000 MΩ
 - ◆ 接触电阻: ≤10 mΩ
 - ◆ Contact resistance: ≤10 mΩ
- 材料 MATERIAL
 ◆ 磷青铜
 PHOSPHOR BRONZE
- 备注: 过盐雾4小时

 JIMDA ® Dongguan Jimda Electronics Co., Ltd 东莞市津达电子有限公司	GENERAL TOLERANCE		SCALE: 5:1	DRAWN: 罗声荣	DATE: 2020. 10. 08	DOC. NO:	TITLE: 工程图	REV. A1
	XX ±0.40		UNIT: mm	CHECK: 于腾	DATE: 2020. 10. 08	PARTS NO: VH-TE	SHEET: 1/1	
X ±0.30		SIZE: A4	APPROVE: 肖志军	DATE: 2020. 10. 08				
X ±0.25								
.XX ±0.15								

DWG NO: E:\DWG\Production\VH

A

B

C

D

E

3

2

1

3

2

1