



## BAX-R4U0

### 4U Rackmount Chassis

- > 4U Rackmount
- > Up to 12"(W) x 9.6"(D) ATX compliant MB
- > 3 x 3.5" Internal Drive Bay
- > 2 x 3.5" + 3 x 5.25" External Drive Bay
- > 7 x Full Height expansion slots
- > 500W PS2 100-240Vac Power Supply
- > Dimension 515 x 430 x 174.8 mm
- > Net weight: 12.09kg(Chassis only)

#### + Spec

-System Information-	
<b>Processor</b>	Depend on MB
<b>Platform Controller Hub</b>	Depend on MB
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec./min. 1sec. or 1min. step
<b>H/W Status Monitor</b>	CPU temperature monitoring Voltages monitoring CPU fan speed control
<b>TPM</b>	Onboard Infineon SLB9665 support TPM 2.0
<b>SBC</b>	ATX MB
-Front I/O-	
<b>USB Port</b>	2 x USB 2.0
<b>Power Button</b>	System power on/off
<b>Reset Button</b>	System reset
<b>LED Indicator</b>	Power status, HDD, LAN activity LEDs
Expansion	
<b>Expansion</b>	7 x Full Height expansion slots on chassis
Storage	
<b>Storage</b>	3 x 3.5" Internal Drive Bay 2 x 3.5" + 3 x 5.25" External Drive Bay
Power Requirement	
<b>Adapter</b>	500W PS2 100-240Vac Power Supply
Mechanical & Environmental	
<b>Operating Temperature</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temperature</b>	-30°C ~ 70°C (-22°F ~ 158°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	515 x 430 x 174.8 mm
<b>Construction</b>	Metal
Ordering Information	
<b>Ordering Information</b>	BCC-CASE-R4U0-02R 4U Rackmount Chassis(without 500W PSU) ACC-PSU-500N-01R Power Supply ATX 500W