Product Specification

| Number: | RNP18-NR6045-100M |
|---------|-------------------|
| | |

Fixed inductors for surface mounting Name:

Customer:

Date: 2023-07-21

| Customer Signature: | | |
|---------------------|--|--|
| | | |
| | | |
| | | |



| Compi | Check | Review | Approva |
|-------|--------|--------|---------|
| Jenny | Jack.C | | |

| Part name | Fixed inductors for surface mounting | Date | 2023-07-21 |
|-------------|--------------------------------------|---------|------------|
| Part number | RNP18-NR6045-100M | Edition | V1 |
| Department | | Page | 1/2 |

Revision Status

| Version | Date | Revision Description | Prepared | Checked | Approved |
|---------|------|----------------------|----------|---------|----------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |



| Part name | Fixed inductors for surface mounting | Date | 2023-07-21 |
|-------------|--------------------------------------|---------|------------|
| Part number | RNP18-NR6045-100M | Edition | V1 |
| Department | | Page | 2/2 |

FEATURES:

- ·Excellent solderability and high heat resistance.
- ·Suitable for large currents.
- ·Is applicable to a wide range of DC-DC converters ideal For (DVD;DSC;phone; PDA;GPS;CMMB;


Digital photo, Frame, telephone; CAR AV equipment and so on.)


Current Rating: Based on the largest decline in ICP to 35 percent, and the temperature does not exceed 40 degrees.

·Measuring frequency: 100KHz/0.25V

DIMENSIONS(mm):

LAND PATTERNS(mm):





| Type 型号 | Indicate 表示 | Inductance 电感量(µH) | D. C. R(Max) 直流电阻(mΩ) | Saturation Current 饱和电流 (A) |
|-------------|----------------|----------------------------|--------------------------|--------------------------------|
| NR6045-1R0N | 1R0 | 1.0µH±30% | 18 | 8. 5 |
| NR6045-1R5N | 1R5 | 1.5µH±30% | 21 | 8. 0 |
| NR6045-2R2M | 2R2 | 2.2µH±20% | 27 | 6. 0 |
| NR6045-3R3M | 3R3 | 3.3µH±20% | 35 | 5. 0 |
| NR6045-4R7M | 4R7 | 4.7µH±20% | 40 | 4. 0 |
| NR6045-6R8M | 6R8 | 6.8µH±20% | 55 | 3. 6 |
| NR6045-100M | 100 | $10 \mu H \pm 20\%$ | 61 | 3. 0 |
| NR6045-150M | 150 | 15µH±20% | 100 | 2. 3 |
| NR6045-220M | 220 | 22µH±20% | 149 | 1. 9 |
| NR6045-330M | 330 | 33µH±20% | 188 | 1.5 |
| NR6045-470M | 470 | $47 \mu \text{H} \pm 20\%$ | 286 | 1.3 |
| NR6045-680M | 680 | 68µH±20% | 429 | 1.0 |
| NR6045-101M | 101 | $101 \mu H \pm 20\%$ | 650 | 0.8 |