

463BS6

Wall mounted inlet

2CMA167566R1000



Surface Inlet, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

GENERAL

| | |
|----------------------------|--------------------------------------|
| Product Name | Wall mounted inlet |
| Product ID | 2CMA167566R1000 |
| Function | Surface inlet |
| EAN | 7392696675666 |
| Catalog Description | Surface inlet, 6h, 63A, IP44, 3P+N+E |
| Country of Origin | Czech Republic (CZ) |
| E-Number Finland | 2421526 |
| E-Number Norway | 2417207 |
| E-Number Sweden | E2417207 |
| Standards | IEC 60309-1, -2 |
| RoHS Status | Following EU Directive 2011/65/EU |

TECHNICAL

| | |
|-----------------------------|--------------------------|
| Product Main Type | TBS |
| Color | Red |
| Number of Poles | 5 |
| Clock Position | 6Hour |
| Rated Current | 63 ampere |
| Rated Voltage | 200/346 ... 240/415 volt |
| Frequency | 50 hertz 60 hertz |
| Degree of Protection | IP44 |
| Cable Cross-Section | 6...25 mm ² |
| Housing Material | Plastic (PA) |
| Plug Angle | Angled |
| Product Group | Tough&Safe |

DIMENSIONS

| | |
|---------------------------|----------------|
| Product Net Width | 107 millimetre |
| Product Net Height | 117 millimetre |
| Product Net Length | 237 millimetre |
| Product Net Depth | 237 millimetre |
| Product Net Weight | 0.85 kilogram |

PACKAGING

| | |
|-----------------------------|----------------|
| Package Width | 152 millimetre |
| Package Height | 265 millimetre |
| Package Gross Weight | 0.94 kilogram |
| Package Length | 120 millimetre |
| Package Units | box 1 piece |