

432MVS6WH

Industrial Switched Interlocked Socket Outlet

2CMA163285R1000

Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+neutral+earth



GENERAL

Product Name	Industrial Switched Interlocked Socket Outlet
Product ID	2CMA163285R1000
Function	Switched Interlocked Socket outlet, vertical, Heavy Duty
EAN	73926966328
Catalog Description	Switched interlocked socket-outlet, vertical, 6h, 32A, IP67, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2420298
E-Number Norway	2417156
E-Number Sweden	E2417156
Standards	IEC 60309-1, -2, -4
RoHS Status	Following EU Directive 2011/65/EU

DIMENSIONS

Product Net Width	160 millimetre
Product Net Height	205 millimetre
Product Net Length	307 millimetre
Product Net Depth	307 millimetre
Product Net Weight	1.83 kilogram

TECHNICAL

Product Main Type	CMVS
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	32 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz 60 hertz
Degree of Protection	IP67 IP69
Cable Cross-Section	2.5...10 mm ²
Housing Material	Thermoplastic (PBT)
Plug Angle	
Product Group	Critical&Safe

PACKAGING

Package Width	215 millimetre
Package Height	165 millimetre
Package Gross Weight	1.83 kilogram
Package Length	335 millimetre
Package Units	box 1 piece