



■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000MΩ min
- Temperature Range : - 40°C to +105°C
- Contact Resistance : 20mΩ max

■ HOUSING

- Part No. : JS-1108X-XX
- Plastic:
 - Blank:Noryl
 - A:PBT
- Poles : 1-50 (Single Row)
- Material : High Temp. Plastic
- Q' ty : 1000 pcs./Bag

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
1	—	2.65	26	63.50	66.24
2	2.54	5.28	27	66.04	68.78
3	5.08	7.82	28	68.58	71.32
4	7.62	10.36	29	71.12	73.86
5	10.16	12.90	30	73.66	76.40
6	12.70	15.44	31	76.20	78.94
7	15.24	17.98	32	78.74	81.48
8	17.78	20.52	33	81.28	84.02
9	20.32	23.06	34	83.82	86.56
10	22.86	25.60	35	86.36	89.10
11	25.40	28.14	36	88.90	91.64
12	27.94	30.68	37	91.44	94.18
13	30.48	33.22	38	93.98	96.72
14	33.02	35.76	39	96.52	99.26
15	35.56	38.30	40	99.06	101.80
16	38.10	40.84	41	101.60	104.34
17	40.64	43.38	42	104.14	106.88
18	43.18	45.92	43	106.68	109.42
19	45.72	48.46	44	109.22	111.96
20	48.26	51.00	45	111.76	114.50
21	50.80	53.54	46	114.30	117.04
22	53.34	56.08	47	116.84	119.58
23	55.88	58.62	48	119.38	122.12
24	58.42	61.16	49	121.92	124.66
25	60.96	63.70	50	124.46	127.20

 喬訊電子工業股份有限公司 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.	APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD		DATE
	張育瑞		mm	.0	±0.3	△	尺寸說明欄修正		05/01/07
PART NO JS-1108X-XX 2.54mm Center Mini Latch Housing	CHECKED BY	PROJ	VER NO.	.00	±0.2	△	變更原因遺失		05/11/17
	黃科源		a4	.000	±0.1	△	增加1PIN的規格		10/07/05
DRAWN BY 王誠賢	DATE	SIZE	ANGLE		Conforms to The RoHS Instruction	CUSTOMER			
	2010/07/20	A4	0°	±					
				.0°	±				