



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ HOUSING

- Part No. : JS-1136-XX
- Poles : 2 - 15
- Material : Nylon 66 UL94V-2
- Q' ty: 1,000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-1136-02	2.50	6.00
3	JS-1136-03	5.00	8.50
4	JS-1136-04	7.50	11.00
5	JS-1136-05	10.00	13.50
6	JS-1136-06	12.50	16.00
7	JS-1136-07	15.00	18.50
8	JS-1136-08	17.50	21.00
9	JS-1136-09	20.00	23.50
10	JS-1136-10	22.50	26.00
11	JS-1136-11	25.00	28.50
12	JS-1136-12	27.50	31.00
13	JS-1136-13	30.00	33.50
14	JS-1136-14	32.50	36.00
15	JS-1136-15	35.00	38.50



喬訊電子工業股份有限公司

CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林宗		mm	.0 ±0.3	ECR	RoHS Compliant	06/04/01			
CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	200810-005	08/10/22			
			.000 ±0.1						
			ALL ±						
			ANGLE						
			0° ±						
			.0° ±						
Part No	JS-1136-XX							CUSTOMER	
2.50mm Crimp Style Connectors Housing	黃科源	2008/10/22	A4					Conforms to The RoHS Instruction	

Part No JS-1136-XX
2.50mm Crimp Style Connectors Housing