

# eBOX620-823-FL

Fanless Embedded System with Intel® Atom™ Processor Z510PT/Z520PT



Front view



Rear view

## Specifications

Standard Color	Silver-Black
Construction	Aluminum extrusion and heavy-duty steel
CPU	Intel® Atom™ processor Z510PT 1.1 GHz or Z520PT 1.3 GHz
System Memory	1 x 200-pin DDR2 SODIMM max. up to 2 GB
Chipset	Intel® SCH US15WPT
BIOS	AMI 8Mbit with RPL/PXE LAN boot ROM
System I/O Outlet	2 x RS-232 (COM 1/2) 1 x VGA 1 x Audio (Mic-in/Line-out) 1 x PS/2 keyboard/mouse 1 x 10/100/1000Mbps Ethernet 4 x USB 2.0 1 x SMA type connector opening for Antenna 1 x V <sub>bc</sub> power input connector 1 x ATX power switch
Watchdog Timer	255 levels, 0 - 255 sec.
Storage	1 x 2.5" SATA HDD drive bay 1 x CompactFlash™
Expansion Interface	1 x PCI Express Mini Card (USB signal)
System Indicator	1 x green LED for system power-on 1 x orange LED for HDD active
Power Supply	12V - 24V <sub>bc</sub> -in 36W
Operating Temperature	-20°C ~ +65°C (-4°F ~ +149°F) (with W.T. CF)
Temperature	-20°C ~ +60°C (-4°F ~ +140°F) (with W.T. HDD)
Storage Temperature	-20°C ~ +80°C (-4°F ~ +176°F)
Humidity	10% - 90% , non-condensing
Vibration Endurance	1 Grms with HDD (5 - 500 Hz, X, Y, Z directions)
Dimensions	200 mm (7.87") (W) x 120 mm (4.72") (D) x 56 mm (2.2") (H)
Weight (net/gross)	1.8 kg (3.97 lb)/2.6 kg (5.73 lb)
Certification	CE
EOS Support	XPE, CE, Linux

\* XPE: Windows® XP Embedded

## Packing List

1 x quick manual
1 x driver CD
1 x Y cable for PS/2 keyboard/mouse
1 x screw pack
4 x foot pad
1 x CF mylar

## Features




- Supports Intel® Atom™ processor Z510PT/Z520PT onboard
- Intel® SCH US15WPT chipset with I/O controller
- Supports wide operating temperature of -20°C ~ +65°C
- Fanless operation design with full feature I/O
- High performance DDR2 SODIMM max. up to 2 GB
- One 2.5" SATA HDD drive bay and CompactFlash™ slot

## Ordering Information

Standard	
eBOX620-823-FL -1.3 G	Fanless embedded system with Intel® Atom™ processor Z520PT 1.3 GHz
eBOX620-823-FL -1.1 G	Fanless embedded system with Intel® Atom™ processor Z510PT 1.1 GHz
Optional	
2.5" SATA HDD	40 GB - 512 GB
DDR2 SODIMM	256 MB - 2 GB
Compact flash	256 MB - 8 GB
Din rail kit	
Wall mount kit	
VESA mount kit	

\*Specifications and certifications are limited to optional.

## Dimensions



Embedded Systems

Embedded Field Controllers

Embedded MicroBoxes

Industrial Barebone Systems

Industrial Chassis

Industrial Workstations

Backplanes

Power Supplies

Peripherals & Accessories