



技术参数/Specifications		
额定参数/Rating	1A 12VDC	
环境温度/Environment Temperature	-25°C ~ 85°C	
接触电阻 Contact Resistance	≤ 30mΩ	
绝缘电阻/Insulation Resistance	> 100MΩ (at 500VDC)	
耐电压 Withstand Voltage	针脚-针脚 Terminal-Terminal	500V AC/10mA/5s
	针脚-手柄 Terminal-knob	
电气寿命 Electronical life	5000 Cycles	
操作力 Operating Force	5 ~ 8N (0.3 ~ 3.0kgf)	

NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 .X ± 0.20 .XX ± 0.10

借(通)用件登记
旧底图总号
底图总号
签名
日期

					成品图 PRODUCT DRAWING				浙江佳龙电子有限公司 ZHEJIANG JIALONG ELECTRON CO., LTD		
									DC 插座 DC power socket		
标记 MARK	处数 NO.	更改文件号 REVISE FILE NO.	签名 SIGNATURE	日期 DATE	投影 PROJECTION	版次 REV.	重量 WT.	比例 SCALE	DC-023		
设计 DESIGN			标准化 STANDARDIZATION		第一角 第一分角 A0		4:1 (A4)				
审核 CHECKED			批准 APPROVE								
工艺 TECHNOLOGY			日期 DATE		共 1 页 ALTOGETHER 1 PAGES		第 1 页 THE 1 PAGE				