



29×12.7×15.7

NT75

UL E158859 VDE 40020063 R50157181 CCC 08001023388

Features

- Small size, lightweight.
- Low coil consumption.
- Switching capacity up to 20A.
- PC board mounting.
- Suitable for household electrical appliances, automation system, electrical equipment, instrument, meter telecommunication facilities and remote control facilities.

Ordering Information

NT75 C S 12 DC12V 0.25 3.5 N G
 1 2 3 4 5 6 7 8 9

1 Part number:NT75	5 Coil rated voltage(V): DC:5,6,9,12,24,48,60,110
2 Contact arrangement:A:1A;C:1C;C2:1C2;2A:2A;2C:2C	6 Coil power consumption: 0.25;0.25W;0.41;0.41W;0.72;0.72W
3 Enclosure:S: Sealed type; Z: Dust cover	7 Pole-distance: 3.5;3.5mm;5.0;5.0mm
4 Contact rating:12A,16A/250VAC 30VDC; NO:20A/277VAC,NC:16A/277VAC 2A,2C(0.41W):8A/250VAC 30VDC;8A,10A/277VAC	8 Contact material: NiL:AgSnO ₂ N:AgNi
	9 Contact plating: Nil:Standard; G:Gold plated

Contact Data

Contact Arrangement	1A (SPSTNO) 1C (SPDT(B-M)) 2A (DPSTNO) 2C (DPDT(B-M))	
Contact Material	AgNi AgSnO ₂	
Contact Rating (resistive)	1A,1C:12A,16A/250VAC,30VDC (rushing current 80A) NO:20A/277VAC NC:16A/277VAC 2A,2C(0.41W):8A/250VAC,30VDC 8A,10A/277VAC	
Max. Switching Power	480W 5600VA 2C:2×150W 2×1800VA	
Max. Switching Voltage	125VDC 440VAC	Max. Switching Current:20A
Contact Resistance or Voltage drop	<100mΩ	Item 4.12 of IEC 61810-7
Operational life	Electrical	10 ⁵ Item 4.30 of IEC 61810-7
	Mechanical	10 ⁷ Item 4.31 of IEC 61810-7

Coil Parameter

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (70%of rated voltage)	Release voltage VDC(min) (10% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
005-250 006-250 009-250 012-250 024-250 048-250 060-250	5 6 9 12 24 48 60	6.5 7.8 11.7 15.6 31.2 62.4 78	100 144 324 576 2304 9216 12857	3.5 4.2 6.3 8.4 16.8 33.6 42	0.5 0.6 0.9 1.2 2.4 4.8 6.0	0.25	≤10	<5
005-410 006-410 009-410 012-410 024-410 048-410	5 6 9 12 24 48	6.5 7.8 11.7 15.6 31.2 62.4	61 88 198 351 1405 5620	3.5 4.2 6.3 8.4 16.8 33.6	0.5 0.6 0.9 1.2 2.4 4.8	0.41	≤10	<5
060-480 110-480	60 110	78 143	7500/±15% 25200/±15%	42 77	6.0 11.0			
005-720 006-720 009-720 012-720 024-720 048-720	5 6 9 12 24 48	6.5 7.8 11.7 15.6 31.2 62.4	34.7 50 112.5 200 800 3200	3.5 4.2 6.3 8.4 16.8 33.6	0.5 0.6 0.9 1.2 2.4 4.8	0.72	<10	<5

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition

Insulation Resistance	1000MΩ min (at 500VDC)	Item 7 of IEC 60255-5
Dielectric Strength	Between contacts	50Hz 1000V
	Between contact and coil	50Hz 5000V
Item 6 of IEC 60255-5		Item 6 of IEC 60255-5
Shock resistance	100m/s ² 11ms	IEC 68-2-27 Test Ea
Vibration resistance	10~55Hz double amplitude 1.5mm	IEC 68-2-6 Test Fc
Terminals strength	10N	IEC 68-2-21 Test Ua1
Solderability	235°C ± 2°C 3 ± 0.5s	IEC 68-2-20 Test Ta method 1
Ambient Temperature	-40~85°C	
Relative Humidity	85% (at 40°C)	IEC 68-2-3 Test Ca
Mass	11g 12g	

Safety approvals

Safety approval	VDE	UL&CUR	TUV	CQC
Load	1A,1C:16A/250VAC 2A,2C:8A/250VAC	1A,1C:12A,16A/250VAC, 12A/30VDC(1C) 2A,2C:8A/277VAC,30VDC	1A,1C: NO:20A/277VAC NC:16A/277VAC 2A,2C: 10A/277VAC	1A,1C: 16A/250VAC 2A,2C: 8A/250VAC

Dimensions

Dimension

Mounting (Bottom view)

Wiring diagram (Bottom view)

1A 1C 1A 1C 2A 2C

NOTES 1).Dimensions are in millimeters.
 2).Inch equivalents are given for general information only.

Reference Data

