

## 20.0MM ELLIPTICAL TIR

<b>Status</b>	Production
<b>Part no.</b>	10197
<b>Drawing no.</b>	60432
<b>Product type</b>	Optic
<b>Type</b>	TIR
<b>Pieces</b>	1
<b>Diameter</b>	20.0
<b>Height</b>	9.90
<b>Beam</b>	Elliptical
<b>Flange</b>	Yes
<b>Files</b>	<a href="#">Customer drawing (PDF)</a> <a href="#">Customer 3D model (.igs)</a>



LEDs & Performances	Eff.	FWHM	Cd/lm	Spot	Cross-section	Files
Lumileds Luxeon Rebel Cool White	82.0%	48 x 9.5	6.0			10197_rebel_white_250408.ies
Lumileds Luxeon Rebel Neutral White	84.8%	47.8 x 8.8	6.0			10197_rebel_neutral_white_250408.ies
Lumileds Luxeon Rebel Warm White	82.1%	48.5 x 8.6	6.7			10197_rebel_warm_white_250408.ies
Cree MC-E XLamp® White	81.0%	44 x 23	2.3			10197_Cree_MCE_white_250408.ies
Cree XP-E XLamp® White	86.0%	47 x 8	6.5			10197_cree_xpe_white_250408.ies
Osram Golden Dragon W5SG Dragon White	87.0%	40X10	5.0			10197_Dragon_W5SG_White_250408.Idt 10197_Dragon_W5SG_White_250408.ies
Osram Platinum Dragon W5SN Dragon White	89.0%	47x8	6.7			10197_PlattDragon_W5SN_wht_250408.Idt 10197_PlattDragon_W5SN_wht_250408.ies
Osram Golden Dragon W5SM Dragon White	87.0%	39x7.8	6.0			10197_Dragon_W5SM_White_250408.Idt 10197_Dragon_W5SM_White_250408.ies
SSC A2 Acriche White	83.1%	45.1 x 20.6	3.1			10197_seoul_Acriche2000_cWhite_250408.ies
Nichia NFSW 036 Top Emitting Cool White	87.0%	47.5x7.4	5.7			10197_Nichia_036_CoolWhite_250408.ies
Nichia WS6W 083 Top Emitting Cool White	84.2%	44.6x12.5	3.8			10197_Nichia_083_CoolWhite_250408.ies
Nichia NS3W 183T Top Emitting White	86.8%	48.9x14.3	3.8			10197_Nichia_183_White_250408.ies

Stanley 1643 3U Cool White	82.4%	45.9 x 20.3	3.1			10197_SCW1643US_cool white_250408.ies
Stanley 1653 3U Warm White	82.8%	44.8 x 19.4	3.6			10197_SCW1653US_warm white_250408.ies
Samsung WH5 White	86.5%	47.6 x 16.7	3.2			10197_Sunnix Samsung_SLHNN WH5_cWhite_250408.ies
Lumileds ES Luxeon Rebel Cool White	81.2%	47.8 x 12.7	4.8			10197_Luxeon_Rebel_ES_cool_white_040311.ies

Related Holders & LEDs	Cree MC-E XLamp® White	Cree XP-E XLamp® White	Lumileds ES Luxeon Rebel Cool White	Lumileds Luxeon Rebel Cool White	Lumileds Luxeon Rebel Neutral White	Lumileds Luxeon Rebel Warm White	Nichia NFSW 036 Top Emitting Cool White	Nichia NS3W 183T Top Emitting White	Nichia WS6W 083 Top Emitting Cool White	Osram Golden Dragon W5SG Dragon White	Osram Golden Dragon W5SM Dragon White	Osram Platinum Dragon W5SN Dragon White	Samsung WH5 White	SSC A2 Acriche White	Stanley 1643 3U Cool White	Stanley 1653 3U Warm White
10148 20.0mm Circular Black										✓	✓	✓				
10148-TS 20.0mm Self Adhesive (TS) Black										✓	✓	✓				
10149 20.0mm Circular Clear										✓	✓	✓				
10149-TS 20.0mm Self Adhesive (TS) Clear										✓	✓	✓				
10150 20.0mm Circular White										✓	✓	✓				
10150-TS 20.0mm Self Adhesive (TS) White										✓	✓	✓				
10235 20.0mm Circular Black			✓	✓	✓	✓										
10235-TS 20.0mm Self Adhesive (TS) Black			✓	✓	✓	✓										
10236 20.0mm Circular White			✓	✓	✓	✓										
10236-TS 20.0mm Self Adhesive (TS) White			✓	✓	✓	✓										
10237 20.0mm Circular Clear			✓	✓	✓	✓										
10237-TS 20.0mm Self Adhesive (TS) Clear			✓	✓	✓	✓										
10276 50.0mm Triple White	✓									✓	✓	✓				
10278 50.0mm Triple White									✓							
10279 50.0mm Triple White		✓	✓	✓	✓	✓	✓									
10286 50.0mm Triple White	✓									✓	✓	✓				
10288 50.0mm Triple White									✓							
10289 50.0mm Triple White		✓	✓	✓	✓	✓	✓									
10296 50.0mm Triple Black	✓									✓	✓	✓				
10298 50.0mm Triple Black									✓							
10299 50.0mm Triple Black		✓	✓	✓	✓	✓	✓									
10306 50.0mm Circular Black	✓									✓	✓	✓				
10308 50.0mm Triple Black									✓							
10309 50.0mm Triple Black		✓	✓	✓	✓	✓	✓									

10431 20.0mm Hexagonal Black			✓	✓	✓	✓												
10432 20.0mm Hexagonal Clear			✓	✓	✓	✓												
10433 20.0mm Hexagonal White			✓	✓	✓	✓												
10434 20.0mm Hexagonal Black			✓	✓	✓	✓												
10435 20.0mm Hexagonal Clear			✓	✓	✓	✓												
10436 20.0mm Hexagonal White			✓	✓	✓	✓												
10566 20.0mm Circular Black	✓								✓									
10566-TS 20.0mm Self Adhesive (TS) Black	✓								✓									
10567 20.0mm Circular White	✓								✓									
10567-TS 20.0mm Self Adhesive (TS) White	✓								✓									
10568 20.0mm Circular Clear	✓								✓									
10568-TS 20.0mm Self Adhesive (TS) Clear	✓								✓									
10615 20.0mm Circular Black										✓								
10615-TS 20.0mm Self Adhesive (TS) Black										✓								
10616 20.0mm Circular Clear										✓								
10616-TS 20.0mm Self Adhesive (TS) Clear										✓								
10617 20.0mm Circular White										✓								
10617-TS 20.0mm Self Adhesive (TS) White										✓								
10631 20.0mm Universal White																✓	✓	
10638 20.0mm Universal White								✓										
10640 20.0mm Universal White												✓						
10651 20.0mm Universal White																✓	✓	
10658 20.0mm Universal White								✓										
10660 20.0mm Universal White												✓						
10671 20.0mm Universal White																✓	✓	
10678 20.0mm Universal White								✓										
10680 20.0mm Universal White												✓						
10691 20.0mm Universal Black																✓	✓	
10698 20.0mm Universal Black								✓										
10700 20.0mm Universal Black												✓						
10711 20.0mm Universal Black																✓	✓	
10718 20.0mm Universal Black								✓										
10720 20.0mm Universal Black												✓						
10731 20.0mm Universal Black																✓	✓	
10738 20.0mm Universal Black								✓										
10740 20.0mm Universal Black												✓						
47.313.1101.80 with 47.313.-320.80 20.0mm BJB® Black											✓	✓	✓					

47.313.2401.80 with 47.313.320.80 20.0mm BJB@ Black			✓	✓	✓	✓													
47.313.5201.80 with 47.313.-320.80 20.0mm BJB@ Black		✓																	

Carclo Optics endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct and up to date information, Carclo suggest using the Opticselect tool on our website

<http://www.carclo-optics.com>.

Copyright © Carclo 2010

### General Instruction - Optics & Holders

#### Handling instructions

- Do not handle or install lenses without wearing gloves, skin oils may damage the lens or the light transmission.
- Clean lenses with a mild soap and water and dry with a clean soft cloth.
- Do not use any commercial solvents on lenses.
- Mount holders with low Odour epoxies and allow time for them to out gas to stop lenses fogging.

### Disclaimer - Optics & Holders

Please note that flow lines, weld lines, surface scratches and small black or white inclusions within the lenses are acceptable if the optical performance of the lens is within the specification described below:

For optics that have FWHMs of 20 degrees or less, the general tolerance is +/-2 degrees OR the tolerances stated below - whichever is the greater.

#### For all optics except Rippled and Frosted;

- FWHM = Datasheet Value +/-10%.

#### For all Rippled and Frosted Optics;

- FWHM = Datasheet Value +/-20%

#### For all Optics;

- Efficiency = Datasheet Value +infinity / -10%

The yellowing / browning of polycarbonate lenses and holders can occur due to the natural ageing process and exposure to heat and UV and as such is not covered by Carclo's warranty.

### General Instruction - Taped Holders

#### Click here to view the 3M Technical Data Sheet

- When assembling the pre-taped holder onto the mating surface, the application must be made straight and square, so that the tape bonds consistently with mating surface. Assembly at an angle might cause an imperfect bond to the mating surface.
- Remember to ascertain the compatibility of the different substrates with the tape, as humidity and temperature fluctuations will weaken it's adhesive.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry, free from grease and dirt and must be well unified.
- Some typical surface cleaning solvents are isopropyl alcohol or heptane. \*
- \* *If cleaning of PCB or LED surfaces is required, please follow strictly the cleaning instructions recommended by your PCB and/or LED manufacturer - this is important to note, as cleaning in some circumstances can damage LEDs or other electronic components on the PCB. Please also note that optical components should not be cleaned using any chemicals - only a micro fibre cloth should be used to remove fingerprints or other traces from handling.*
- \* *Carefully read and follow the manufacturer's precautions and directions for use when working with solvents. These cleaning recommendations may not be compliant with the rules of certain Air Quality Management Districts in California; consult applicable rules before use.*

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure and moderate heat, from 100°F (38°C) to 130°F (54°C), will assist the adhesive in developing intimate contact with the bonding surface.

Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C)

Carclo Optics 103 Buckingham Ave, Slough, Berkshire, SL1 4PF ENGLAND

Tel: +44 (0)1753 575011 Fax: +44 (0)1753 811359

is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

During assembly the optic when placed on the PCB should be firmly held for 1-5 seconds to ensure the best possible bond. The tape will reach its final strength in 72 hours, dependent on the material and ambient conditions.

We request that the customer ensures (and fully tests) the suitability and sufficiency of the bond in his product. For example, mechanical stress, vibration and holes on the surface of the circuit board can weaken the strength of the tape.

#### **Disclaimer - Taped Holders**

Shelf Life - There is 1 year expected shelf life from the date of purchase direct from Carclo.

All Carclo lenses supplied with tape use the same high strength double-coated tape (unless otherwise mentioned in the datasheet). This tape is specifically selected for this application.

These tapes generally work well together with PCBs and LEDs on the market. The customer must take the necessary measures to ensure complete compatibility with their particular application, product, PCB, LED and/or other components.

**Testing and verifying of the adhesives and their combinations is the responsibility of the customer.**

The customer is solely responsible for evaluating the application of double sided tape to Carclo Holders and the adhesion of double sided tape holders to determine whether such double-sided tape is fit for a particular purpose and suitable for the users method of application. The selection of double-sided tape in the adhesion of double sided tape holders is not covered by Carclo's warranty.

Carclo cannot take responsibility for the results obtained by others whose methods we cannot control. It is always the customer's responsibility to determine the adhesive's suitability for their product and to take precautions for protection of property and persons against any hazards that may be involved in the handling and use of adhesives. Carclo disclaims all warranties, including warranties of merchantability or suitability for a particular purpose, arising from use of any adhesive product. Carclo disclaims any liability for consequential or incidental damages of any kind, including lost profits.

All rights reserved. No part of this publication may be copied, reproduced in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, illustrations not to be removed, without our prior permission. Carclo Optics reserves the right to make changes at any time in order to supply the best products possible.