

电气性能/Electrical

参考标准/Standard: UL IEC
 额定电压/Rated voltage: 300V 320V
 额定电流/Rated current: 15A 20A
 接触电阻/Contact resistance: $20m\Omega$
 耐电压/Withstanding voltage: AC2000V/1Min
 绝缘电阻/Insulation resistance: $500M\Omega/DC500V$

机械性能/Mechanical

温度范围/Temp.Range: $-40^{\circ}C \sim +105^{\circ}C$
 瞬间温度/MAX Soldering: $+250^{\circ}C$, for 5 Sec

尺寸/Dimensions

间距/Pitch: 5.08mm
 极数/Poles: 2P-24P

材质及电镀/Material

塑件/Housing: PA66, UL94V-0
 焊针/Pin header: Brass, Tin plated

订购方式:
HOW TO ORDER

ULO-TB - - P - - - -

证书系列号/
Certificate Series No.

工厂型号/
Factory Code

位数/Poles

0:一字螺丝/Slot Screw
1:十字螺丝/Cross Screw


0:锁紧/Screw Down
1:退锁/Screw Up

客户要求/
Customer Require

灰色/Grey	1	绿色/Green	4	透明/Transparent	7
蓝色/Blue	2	橙色/Orange	5	黄色/Yellow	8
黑色/Black	3	红色/Red	6	白色/White	9

TOLERANCES EXCEPT AS NOTED

		linear dimension(Tolerances Standard GB/T 14486-2008)										\equiv	$-$	\square	$//$	\perp
variable range	to	over 6 to 6	over 10 to 10	over 18 to 18	over 30 to 30	over 50 to 50	over 80 to 80	over 120 to 120	over 160 to 160	over 200 to 200	over 250 to 250	all	to 5	over 5 to 30	over 30 to 120	over 120 to
	tolerance	± 0.1	± 0.14	± 0.19	± 0.25	± 0.32	± 0.43	± 0.57	± 0.72	± 0.88	± 1.05					

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	比例	第一视角/THIRD ANGLE PROJECTION
 NINGBO ULO ELECTRONICS CO LTD 宁波欧路电子有限公司						名称/NAME ULO-TB27-2VM/5.08