



■ SPECIFICATIONS

- Voltage Rating : 300 - 600V AC/DC
- Current Rating : 9 -15A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min.
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max.

■ TERMINAL

△ Part No. : JS-2000H-TX

① Applicable wires : TH : AWG# 14 - 18
TL : AWG# 18 - 22

- Material : Brass
- Finish : Tin plated
- Thickness : 0.25mm
- Q' ty : JS-2000H-TH : 3,500 pcs./Reel
JS-2000H-TL : 5,000 pcs./Reel

Part No.	Dimensions(mm)±0.4			
	A	B	C	D
JS-2000H-TH	4.80	4.85	2.90	3.70
JS-2000H-TL	4.10	3.20	2.60	2.30



喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-2000H-TX

2.00mm Power Connectors Terminal

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	△	刪除舊料號	吳弘文	2013/12/02	△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	修正產品外觀	吳弘文	2013/12/09	△			
黃科源		a2	.000 ±0.10	△				△			
DRAWN BY	DATE	SIZE	ANGLE	△					CUSTOMER		
吳弘文	2013/12/09	A4	0° ±1°	△					Conforms to The RoHS Instruction		
			.0° ±	△							
			SHEET 1/1	△							