



Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA
 Insulator resistance: 1000MΩ min.at DC 500V
 Current Rating: 1AMP

Dielectric Withstanding

Voltage: AC 500V For 1 minute
 Operating Temperature: -55°C---+105°C
 Contact: Brass
 Housing: Nylon 66(UL 94V-0)

| Position | C | D |
|----------|-------|-------|
| 2 | 7.92 | 3.96 |
| 3 | 11.88 | 7.92 |
| 4 | 15.84 | 11.88 |
| 5 | 19.8 | 15.84 |
| 6 | 23.76 | 19.8 |
| 7 | 27.72 | 23.76 |
| 8 | 31.68 | 27.72 |
| 9 | 35.64 | 31.68 |
| 10 | 39.6 | 35.64 |
| 11 | 43.56 | 39.6 |
| 12 | 47.52 | 43.56 |
| 13 | 51.48 | 47.52 |

要求:

1. 塑料件无裂痕。
2. 整排端子成一直线，相邻端子之间相互平行。

| | | | | | |
|----------------|---------------|---------------|----------------|---------------------------|------------|
| 设计/Designed by | 绘图/Drawing by | 审核/Checked by | 批准/Approved by | 未注公差 General Tolerance | |
| | | 图名/Title | 文件编号/File No. | x. ±0.2 | x.' ±2° |
| | | 135M弯针产品图 | 页序/Sheet | .x ±0.1 | .x' ±1° |
| | | 备注/Remark | | .xx ±0.05 | .xx' ±0.5° |
| | | | | .xxx ±0.01 | |
| | | | | 单位/Units: mm | |