

Ordering Information

Circuits	Part No	Dimension(mm/inch)	
		A	B
2	1090-188-020	2.54(.100)	5.08(.200)
3	1090-188-030	5.08(.200)	7.62(.300)
4	1090-188-040	7.62(.300)	10.16(.400)
5	1090-188-050	10.16(.400)	12.70(.500)
6	1090-188-060	12.70(.500)	15.24(.600)
7	1090-188-070	15.24(.600)	17.78(.700)
8	1090-188-080	17.78(.700)	20.32(.800)
9	1090-188-090	20.32(.800)	22.86(.900)
10	1090-188-100	22.86(.900)	25.40(1.000)
11	1090-188-110	25.40(1.000)	27.94(1.100)
12	1090-188-120	27.94(1.100)	30.48(1.200)
13	1090-188-130	30.48(1.200)	33.02(1.300)
14	1090-188-140	33.02(1.300)	35.56(1.400)
15	1090-188-150	35.56(1.400)	38.10(1.500)

Features

Material: PBT, UL94V-0

Color: Black

Specifications

Current Rating: 3A max.

Voltage Rating: 250V AC DC max.

Temperature Range: -25°C~+85°C


Contact Resistance: Initial value 10mΩ max.

After environmental testing 20mΩ max.

Insulation Resistance: 1000mΩ min.

Dielectric Withstanding Voltage: 1000V AC for 60s

DATE 09/08/04
FINAL DATE 09/08/04
UNIT: mm SCALE:



2D FILE D:/standard/S-01053.dwg

3D FILE

DESIGNER

CHECKER

TITLE:
2.54mm (.100") Pitch
FFC/FPC Housing

PART NO.: 1090-188-XX0

DRAWING NO.: S-01053

REV.: A