


Suggested P.C.B Layout

| 技术参数/Specifications | |
|------------------------------|---------------------|
| 额定参数/Rating | 0.1A 12VDC |
| 环境温度/Environment Temperature | -25°C ~ 85°C |
| 接触电阻 Contact Resistance | ≤ 50mΩ |
| 绝缘电阻/Insulation Resistance | ≥ 100MΩ (at 500VDC) |
| 耐电压 Withstand Voltage | 100V AC/10mA/5s |
| 电气寿命 Electrical life | 500V AC/10mA/5s |
| 操作力 Operating force | 100000 Cycles |
| | 260 ± 50gf |

电气原理图:
CIRCUIT:



NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 . X ± 0.20 . XX ± 0.10

| | |
|-----------|--------------------------------|
| 修改/工厂用者登记 | REVISION/FACTORY USER REGISTER |
| 图号 | DRAWING FILE NO. |
| 日期 | DATE |
| 签名 | SIGNATURE |
| 图号 | DRAWING FILE NO. |
| 日期 | DATE |
| 签名 | SIGNATURE |

| | | | |
|------------------------------------|----|------------|----|
| ZHEJIANG JIALONG ELECTRON CO., LTD | | 浙江佳龙电子有限公司 | |
| Tact Switch | | 轻触开关 | |
| 11-TC-06F | | | |
| 图号 | 图次 | 比例 | |
| 11-TC-06F | A0 | 6:1 (A4) | |
| 设计 | 审核 | 制图 | 检查 |
| | | | |
| 日期 | 日期 | 日期 | 日期 |
| | | | |