

# Data Sheet

## LL15ED-BH40L06



**Xlamp MX-6**



### ■ Features & Typical Applications

- High efficiency
- Available with 1 beam angle
- Optimized for uniform effect
- Lens without Housing
- Commercial Lighting
- Architectural Lighting

### ■ Table of Contents


General Information & Product Nomenclature.....	P.2
Optical Specifications .....	P.3
Mechanical Specifications .....	P.4
Package Specifications .....	P.5

# LL15ED-BH40L06

## General Information

- Lens Material Optical Grade PMMA
- Operating Temperature range -40°C~+70°C(upper limit +80°C)
- Storage Temperature range -40°C~+70°C(upper limit +80°C)
  - \* Average transmittance in visible spectrum 400nm~700nm>90%
- Usage and Maintenance:
  1. If necessary, clean lenses with mild soap, water and soft cloth.
  2. Never use any commercial cleaning solvents on lenses, like alcohol.
  3. Please handle or install lenses with wearing gloves, skin oils may damage lens or its optical characteristic.

## Product Nomenclature






# LL15ED-BH40L06

## Optical Specifications



**Xlamp MX-6**

Note: (1) All the results of analysis are based on 0 degrees of elevation.  
 (2) Tolerance:  $\pm 10\%$ .  
 (3) Led Luminous Flux(lm): 78( $\pm 5\%$ ).

Part Number	FWHM	Field Angle*	cd / lm	IES File
LL15ED-BH40L06	25°	54°	2.8	<a href="#">Download</a>
				
Beam Pattern	Light Distribution Curve		Illuminance Distribution	

\*Current series also come with BH25. However, the performance with the LED is not satisfied hence it will not demonstrate here.

\*The Field Angle is the angle between the two directions opposed to each other over the beam axis for which the luminous intensity is 10% that of the maximum luminous intensity.

\*This testing result is obtained through testing the popular rank LED samples which provided by the original manufacturer. Hence, the testing results would be varied as the users choose same LED model but different rank.

# LL15ED-BH40L06


## Mechanical Specification

### 1. Fixing method

- Glue     
  Screw     
  Tape     
  Fixing-ring     
  Frame

Note: (1) All dimensions are in mm.  
 (2) All measurements are  $\pm 0.15$  mm unless otherwise indicated.

### 2. Lens dimensions




### 3. Lens + Leds + MCPCB assembly instruction



### 4. Lens assembly dimensions


### 5. View assembly lens with MCPCB:





# LL15ED-BH40L06

## Package Specifications

Item	Quantity	Total	Size(L*W*H)	G.W
Plastic box	18 pcs/plastic box	18 pcs	38.2*36.2*2.5 cm	40.4g
Outer box	6 plastic box/Outer box	108 pcs	40*37*21 cm	



18 pcs/plastic box



108 pcs/Outer box

Note: