



Circuit	Dimensions(mm)	
	A	B
02	2.00	5.75
03	4.00	7.75
04	6.00	9.75
05	8.00	11.75
06	10.00	13.75
07	12.00	15.75
08	14.00	17.75
09	16.00	19.75
10	18.00	21.75
11	20.00	23.75
12	22.00	25.75
13	24.00	27.75
14	26.00	29.75
15	28.00	31.75
16	30.00	33.75

Material:
Housing:PA66(UL94V-0),White

- Electrical Characteristics:
- 1.Poles: 2 to 20P
 - 2.Current rating: 2.0A
 - 3.Voltage rating: 100V
 - 4.Temperature range: -25℃ to +85℃
 - 5.Contact resistance: $\leq 10m\Omega$
 - 6.Insulation resistance: $\geq 1000M\Omega$
 - 7.Withstand voltage: 800V AC/minute
 - 8.Applicable wire: AWG #30 to #24
 - 9.Applicable PC board thickness: 0.8~.6mm

16&15 11&10 6&5

GENERAL TOLERANCE	PROJECTION		Description:
X. ± 0.50	UNITS	mm	2.00mm Pitch PH type Wire to Board Connector
.X ± 0.25	SCALE	1:1	
.XX ± 0.10	Draw by:	Jenny	P/N: WSxxS-CT
ANGLE TOLERANCE	Check by:		CONNTERM
X. $\pm 5^\circ$	Date	2018-03-01	
.X $\pm 3^\circ$	SHEET	1 OF 1	
.XX $\pm 2^\circ$			