

## ZORYA-SC

~340° decorative beam. Suitable also for UV-C applications.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 56.0 mm
Height	26.7 mm
Fastening	glue, socket
ROHS compliant	yes ⓘ

### MATERIAL SPECIFICATIONS:


Component	Type
ZORYA-SC	Single lens



Material	Colour	Finish
Silicone	clear	

### ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
F15074_ZORYA-SC » Box size: 398 x 298 x 140 mm	140		35	3.0



#### PHOTOMETRIC DATA (MEASURED):


#### CITIZEN

LED CLL02x/CLU02x (LES10)  
FWHM 218.0°  
Efficiency 94 %  
Peak intensity 0.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 434 Typ L7




#### CITIZEN

LED CLL03x/CLU03x  
FWHM 149.0°  
Efficiency 94 %  
Peak intensity 0.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 433 Typ L7




#### CREE

LED CXA/B 25xx  
FWHM 143.0°  
Efficiency 94 %  
Peak intensity 0.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 439 Typ L7



#### NICHIA


LED COB L-Type (LES 11)  
FWHM 189.0°  
Efficiency 94 %  
Peak intensity 0.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 438 Typ L7




#### PHOTOMETRIC DATA (SIMULATED):



LED NCSU334A  
FWHM 224.0°  
Efficiency 64 %  
LEDs/each optic 1  
Light colour UV  
Required components:



LED WICOP DY9560-27  
FWHM 254.0°  
Efficiency 58 %  
LEDs/each optic 24  
Light colour UV  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)