



| SIZE | STUD SIZE | | $B_{\pm 0.1}$ | $L_{\pm 0.3}$ | $F_{\pm 0.2}$ | $\text{Ø}D_{\pm 0.2}$ | $H_{\pm 0.2}$ | | | | |
|------|---------------|--|---------------|---------------|---------------|-----------------------|---------------|--|--|--|--|
| | $d_{\pm 0.1}$ | | | | | | | | | | |
| | 1.7 | | 7.45 | 20.1 | 6.7 | 3.8 | 10.0 | | | | |

| | | Unit | MM (IN) | NO | Technical requirement | Version | | | | | |
|--------------------|--------------------------------------|---------------------|-----------------------|--|--------------------------|---------|-------|----|--|--|--|
| Wire Range | 22-16A.W.G (0.5-1.5mm ²) | | | 1 | No oxidation | 4 | | | | | |
| Voltage | 75 °C 300VOLTS MAX. | | | 2 | No structure deformation | 5 | | | | | |
| Current | 10A | | | 3 | | 6 | | | | | |
| Part No. | FDD1.25-250 | Terminal material | Brass with tin plated | | Made | 高迪 | Check | 杨涛 | | | |
| Drawing No | KT-57125250 | Insulation material | PVC | | | | | | | | |
| Date | 2016. 7. 16 | Color | | 浙江珠城科技股份有限公司 Zhejiang ZUCH Technology CO., Ltd. | | | | | | | |
| Material Thickness | 0.4mm | | | | | | | | | | |