


Suggested P.C.B Layout

技术参数/Specifications	
额定参数/Rating	0.1A 12VDC
环境温度/Environment Temperature	-25°C ~ 85°C
接触电阻 Contact Resistance	≤ 50mΩ
绝缘电阻/Insulation Resistance	≥ 100MΩ (at 500VDC)
耐电压 Withstand Voltage	100V AC/10mA/5s
电气寿命 Electrical life	500V AC/10mA/5s
操作力 Operating force	100000 Cycles
	260gf

电气原理图:
CIRCUIT:



NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 . X ± 0.20 . XX ± 0.10

修改日期/修改记录 MODIFY DATE/REVISION	
审核人/审核日期 CHECKER/DATE	
设计人/设计日期 DESIGNER/DATE	
制图人/制图日期 DRAWING FILE NO./DATE	
零件号 PART NO.	
图号 DRAWING FILE NO.	
图名 TITLE	

<p>成品图 PRODUCT DRAWING</p>		<p>浙江佳龙电子有限公司 ZHEJIANG JIALONG ELECTRON CO., LTD</p>	
设计/DESIGN	审核/CHECKER	重量/WT.	比例/SCALE
制图/DRAWING	日期/DATE	A0	6:1 (A4)
图号/DRAWING FILE NO.	零件号/PART NO.	<p>轻触开关 Tact Switch</p>	
		<p>TC-06F H4.3</p>	